



REV.	DESCRIPTION	APPROVED BY	DATE	ECN NO.
A	RELEASE	KUNG	10/01/11*	
B				
C				

NY-WP331(4P)  
NY-WP484(5P)

1. MATERIAL :
    - 1-1. a. HOUSING : PBT UL94V-0 ; COLOR : BLACK.
    - b. CONTACT : BRASS
    - c. NUT : ALUMINUM ALLOY
    - d. SHELL : ALUMINUM ALLOY
    - e. O-RING : EPDM ; COLOR : BLACK
    - f. Epoxy Base : EF400A&EF400B. COLOR : BLACK.
  - 1-2. Main Body : ALUMINUM ALLOY
  - 1-3. Gland : SILICONE COLOR : BLACK.
  - 1-4. Gland Cage : POM ; COLOR : BLACK.
  - 1-5. Gland Nut : ALUMINUM ALLOY
2. FINISH :
    - 2-1. a. CONTACT : GOLD FLASH MICRO INCHES MIN.  
UNDER PLATE : NICKEL.
    - b. NUT : SATIN Ni PLATED.
    - c. SHELL : SATIN Ni PLATED.
    - 2-2. Main Body : SATIN Ni PLATED.
    - 2-3. Gland Nut : SATIN Ni PLATED.
  3. ELECTRICAL SPECIFICATION :
    - 3-1. Rated current : 5A
    - 3-2. Rated Voltage : 125V
    - 3-3. Water proof : IPX7
  4. Environmental :
    - 4-1. Operation Temperature : -20 ℃~85℃

DRAWN	KU Chau	APP'D	KUNG	UNIT	mm	TOLERANCE		<b>JKL TECHNOLOGY CO., LTD.</b>	TITLE	M12 4PIN(F) A-coded Assembly type		SHEET	
CHK'D	JUSTIN			SCALE	1:1	.x ±0.20 .xx ±0.10 .xxx ±0.05 .xxxx ±0.03 ANGULA ±1°			PART NO.	WP-04F2-62	DWG NO.	QC5210	