



Assembly

1. MATERIAL :
 - 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK
 - 1-2. CONTACT : COPPER ALLOY
 - 1-3. SHELL : COPPER ALLOY
 - 1-4. NUT : COPPER ALLOY
 - 1-5. O-RING : EPDM ; COLOR : BLACK
 - 1-6. Epoxy Base : EF400A&EF400B. COLOR:BLACK
2. FINISH :
 - 2-1. CONTACT : 10 MICRO INCHES MIN. GOLD PLATING OVER NICKEL
 - 2-2. SHELL : NICKEL PLATED 60u" ~ 100u" OVER ALL
 - 2-3. NUT : NICKEL PLATED 60u" ~ 100u" OVER ALL
3. ELECTRICAL SPECIFICATION :
 - 3-1. Rated current : 5A
 - 3-2. Voltage : 125V
 - 3-3. Water proof: IPX7
4. Environmental :
 - 4-1. Operation Temperature : -40 °C~85°C

REV.	DESCRIPTION	APPV. BY	DATE	ECON. NO.
A	RELEASE	KUNING	22/12/08*	
B				
C				

DRAW	HULK	APPVL	KUNING	UNIT	mm	TOLERANCE	JKL TECHNOLOGY CO., LTD.	PART NO.	WP-04M2-12	DWG NO.	QC3228	SHEET
CHECK				SCALE	1:1	x ±0.20 xx ±0.10 xxx ±0.05 xxxx ±0.03 ANGULA ±1°						