



ELECTRICAL:

- CONTACT RESISTANCE: 20M OHMS MAX
- INSULATION RESISTANCE: 250M OHMS @500V DC
- WITHSTAND VOLTAGE: DC1000V AC700V RMS 60HZ, 1MIN
- CAT6 PERMANENT LINK: CONFORM TO ANSI/TIA/EIA 568B. 2-10

ENVIRONMENTAL:

- STORAGE: -40° / +70°
- OPERATION: -10° / +60°

MECHANICAL:

- PLASTIC MATERIAL: PC UL 94-V0
- IDC MATERIAL: PC
- TERMINAL: PHOSPHOR BRONZE, TIN GOLD 3U''/6U''/15U''/30U''/50U''
- RJ45 CONTACT LIFE: 750 TIMES MIN
- IDN LIFE: 250 TIMES MIN

TYPE:

- UNSHIELDED CAT6 TOOLLESS PLUG
- COLOUR: WHITE
- CONDUCTOR SUITABLE: 23AWG~24AWG

REV.	DESCRIPTION	APPROVED BY	DATE	ECN NO.
A	RELEASE	KUNG	2016.07.06	
B				
C				

DRAWN	Ku Chou	APP'D	KUNG	UNIT	mm	TOLERANCE	±0.20 ±0.10 ±0.05 ±0.03
CHK'D	Emily Suen			SCALE	1:1	ANGULA	±1°
		JKL TECHNOLOGY CO., LTD.		TITLE		CAT.6 UTP PLUG-ASS'Y TYPE ,WHITE.	
		PART NO.		DWG.		RJU06-88-VWH RJU06-688Y	
				SHEET		VERSION	
				A		A	