



REV.	DESCRIPTION	APPROVED BY	DATE	ECN NO.
A	RELEASE	KUNG		
B				
C				

1. MATERIAL :

1-1. a. HOUSING : PBT UL94V-0 ; COLOR : BLACK.

b. CONTACT : BRASS

c. NUT : ALUMINUM ALLOY

d. SHELL : ALUMINUM ALLOY

e. O-RING : EPDM ; COLOR : BLACK

f. Epoxy Base : FF400A&FF400B. COLOR : BLACK.

1-2. Main Body : ALUMINUM ALLOY

1-3. Gland : SILICONE COLOR : BLACK.

1-4. Gland Cage : POM ; COLOR : BLACK.

1-5. Gland Nut : ALUMINUM ALLOY

2. FINISH :

2-1. a. CONTACT : GOLD FLASH MICRO INCHES MIN.

UNDER PLATE : NICKEL.

b. NUT : SATING NI PLATED.

c. SHELL : SATING NI PLATED.

2-2. Main Body : SATING NI PLATED.

2-3. Gland Nut : SATING NI PLATED.

3. ELECTRICAL SPECIFICATION :

3-1. Rated current : 5A

3-2. Rated Voltage : 125V

3-3. Water proof : IPX7

4. Environmental :

4-1. Operation Temperature : -20 C~85C

DRAWN	KU Chou	APP'D	KUNG	UNIT	mm	TOLERANCE		JKL TECHNOLOGY CO., LTD.	TITLE	M12 8PINKF	A-coded Assembly type	SHEET	1
CHK'D	JUSTIN	SCALE	1:1	SCALE	1:1	±0.20 ±0.10 ±0.05 ±0.03 ANGULA ±1°			PART NO.	WP-08F2-33	DWG NO.	QC5878	VERSION