



REV.	DESCRIPTION	APPROVED BY	DATE	ECN NO.
A	RELEASE	KUNG		
B				
C				

JKL TECHNOLOGY CO., LTD.

1. MATERIAL :
 - 1-1. a. HOUSING : PBT UL94V-0 ; COLOR : BLACK.
 - b. CONTACT : BRASS
 - c. NUT : ALUMINUM ALLOY
 - d. SHELL : ALUMINUM ALLOY
 - e. Epoxy Base : EF400A&EF400B. COLOR : BLACK.
2. FINISH :
 - 2-1. a. CONTACT : GOLD FLASH MICRO INCHES MIN. UNDER PLATE : NICKEL.
 - b. NUT : SATING NI PLATED.
 - c. SHELL : SATING NI PLATED.
 - 2-2. Main Body : SATING NI PLATED.
 - 2-3. Gland Nut : SATING NI PLATED.
3. ELECTRICAL SPECIFICATION :
 - 3-1. Rated current : 5A
 - 3-2. Rated Voltage : 125V
 - 3-3. Water proof : IPX7
4. Environmental :
 - 4-1. Operation Temperature : -20 t~85t

DRAWN	KU Chou	APP'D	Kung	UNIT	mm	TOLERANCE	 	JKL TECHNOLOGY CO., LTD.	TITLE	M12 8PINKM	A-coded Assembly type	SHEET	1
CHK'D	Justin	SCALE	1:1	xx	±0.20	x xx xxx xxxx ANGULA ±1°			PART NO.	WP-08N2-27	DWG NO.	QCS5876	VERSION